


## Wall Mount CO2 monitor

### Specification

Display mode	LED display
Carbon Dioxide(CO2)	0~9999PPM
Accuracy	±50 ppm or ±5%(0~5000PPM)
Resolution	1PPM
Response time	10s
Repeatability	±20ppm
Formaldehyde	0~1000PPM
Accuracy	±5%
TVOC range	-10~70°C
Temperature Range	±0.5°C/±0.9°F
Temperature Accuracy	0-99.9%RH
Humidity Range	±3%RH(20%RH~80%RH)
Humidity Accuracy	adaptor(DC9v)
Power	0 to 50°C; 10%RH to 90%RH
Operating Environment	-20 to 60C; 10%RH to 75%RH
Sensor life	15 years in normal comm
Size	388×288×43mm
Wight	2420g



HT-2009



## CO2 meter

Carbon dioxide meter is widely used in factory,workshop, green house,clean room,industry and agriculture,wine bar,hotel,hospital,shop market,airport,railway station, entertainment hall and moive theater etc.

### Specification

Large LCD Display	Color display with backlight
Logger mode	key start/stop,Immediately,Schedule,Real-time&Roll-over
Carbon Dioxide(CO2)	
Range	0~9999PPM
Accuracy	±70ppm or ±3% rdg (0~5000PPM)
Response time	1s
Temperature Range	-10~70°C(14~158°F)
Resolution	0.1°C/°F
Accuracy	±0.3°C(10~50°C) ,others ±1.2°C
Humidity Range	0.1~99.9%RH
Resolution	0.1%
Accuracy	±3%(10~90%)
Logging Memory	12700
Operating Condition	0~50°C,0~85%RH (No Condensation)
Storage Condition	-20~60°C,0~99%RH (No Condensation)
Sensor life	15 years in normal comm
Storage temp	-20~60°C,0~90%RH (No Condensation)
Battery	3.7V rechargeable Li-ion polymer battery
Size	107×107×59mm



HT-501

LINE ID: @neonics



ติดต่อบริษัท นีโอนิกส์ จำกัด

Tel: 02-077-7602 หรือ 061-8268939

E-mail: sale@tools.in.th หรือ sale@neonics.co.th