



Radar Speed Meter



Application: It can measure Baseball, Softball, Vehicles, Tennis etc.

Specification

Balls	16~177Km/h (10~110 Miles/h)
Vehicles	16~320Km/h (10~200 Miles/h)
Effective Distance	
For Balls	0~22.5m
For Vehicles	0~390m
Launch Angle	15°
Microwave Frequency	24.15GHz
Measuring Accuracy	±1.0MPH;±2.0KPH
Power Supply	C Type 1.5V*2
Environment Temperature	-10~50°C
Environment Humidity	10%~90% RH

HT-930

PM2.5 Detector



This product is lightweight, you can carry no matter where you go and know the air quality anytime.

Specification

Measuring range	0-1000ug/m ³
Resolution	1ug/m ³
Measuring accuracy	10ug/m ³ (0-100ug/m ³) 10% (100—500ug/m ³)
Operating temperature	0~50°C
Operating humidity	10%~80%RH
Size	55×55×20mm
Weight	75g
Power supply	2*1.5V AAA
Response time	3S
Sensov Type	laser scattering
Alavm function	Intelligent expression vating alarm

HT-403

Digital Tachometer

It is a leakage detector where used in refrigeration,air-condition,storage,restore the container and so on

Specification

Detect R-22 ,R-134,R-404A,R-410A,R-407C,R-502,R-600A,R-123yf...more Refrigerant Gas.
Equal Sensitivity to CFCs,HCFCs and HFCs.
Air sucking System for raster response and higher sensitivity
Microprocessor Control with advanced digital signal processing.
semiconductor gas sensor.
High Low Leak Sensitivity selector
7 LED Tri-colored Visual Leak LevelIndicator
Ambient Concentration Reset
Snake Tube Length:400mm(15.5")flexible stainless probe
Auto power off: 10 minutes
Ambient Concentration reset.
Low battery indication.
Reference Leak source included.
Hard Carrying case included.
Accordance with SAE J1627,CE designFeatures Sensitivity



HT-523

Four in one gas detector

It can be used in mining,metallurgy security ring,petrochemical, power telecommunications,municipal and other occasions.

Specification

Vibration-proof enclosure
2in color display
Detection of gas:H2s/CO/O2(%Volume ratio)/Combustible gas (site selection)
Measurement range:0-100ppm(H2S)/0-500ppm(CO)0-25%(O2)
0-100%LEL(Combustible gases)
Rechargeable Battery
Visual,auditory alarm and buzzer alam
Automatic or mobile phone open, red flashing, vibration
Alarm values can be set
Full function self-test
Size:136mm×68mm×34mm
Weight:250g



HT-1805