

## Humidity & Temperature Meter



Technical indicators		GM1362	
Temperature Range		-30~ 70°C	
Temp Accuracy		±1°C or ±0.2°F	
Humidity measurement range		0 ~ 100%RH	
Value accuracy		±3%(30~95%);±5%(10~30%)	
Temperature resolution		0.1°C	
Humidity resolution		0.1%RH	
Peculiarity		Conventional	
°C/°F Selection	√	Product size	152*35.5*52.5mm
Keeping data	√	Product weight	129.3g (+batteries)
MAX/MIN	√	Power supply	9V batteries
Large screen display	√	Standard Quantity Per Carton	60PCS
Automatic/manual to turn it off	√	Standard Carton Size & gross weight	50*33.7*45kg&12kg



GM1362

Technical indicators	GM1365	GM1366
Measuring range	Temperature:-30~ 80°C Humidity:0 ~ 100%RH	Temperature:-30~ 80°C Humidity:0 ~ 100%RH
Record capacity	32256	61440
Precision	±2%RH	Typical±0.5°C (See Fig 5)
Peculiarity		
MAX/MIN	√	√
Upper/lower limit alarm	√	√
USB	√	√
Sampling period set	√	√
Data storage interval	√	√
SET ALARM	√	√
Bluetooth	×	√
Conventional		
Power supply	1/2AA 3. 6V Li-Ion battery	
Product size	126*28*22mm	
Product weight	58.59g (+batteries)	



GM1365



GM1366

LINE ID:neonicstool



ติดต่อบริษัท เนโอเนิกส์ จำกัด

Tel: 02-077-7602 หรือ 061-8268939

E-mail: sale@tools.in.th หรือ sale@neonics.co.th