



HT-201

## PH Meter

PH meter is widely used in environmental protection sewage treatment,standy,Pharmacy,Fermentation, Chemical,breed aquatics,Domestic water and so on

### Specification

Measuring range	0.00~14.00Ph
Measuring error	±0.1Ph
Resolution	0.1Ph
Display	3 digits
Temperature compensation	5~50°C
One point calibration	
Power supply	3V (CR2032)
Size	148×33.8×19mm
Weight	65.8g



HT-202

## Conductivity Meter

Conductivity meter is not only can test conductivity of liquid but also the high purity water.


### Specification

Measuring range	0~1999μS/cm
Resolution	1μS/cm
Accuracy	±2%
LCD Display	4 digits
Automatic Temperature Compensation	0~50°C (32~122°F)
Operating Temperature	0~50°C (32~122°F)
Power supply	3V (CR2032)
Size	148×33.8×19mm
Weight	65.8g

## Wall Mount CO2 monitor

### Specification

Display mode	LED display
Carbon Dioxide(CO2)	0~9999PPM
Accuracy	70ppm ±3%
Resolution	1ppm
Response time	<10s
Repeatability	±20ppm
Temperature Range	-40~1250°C/ (104~257°F)
Temperature Accuracy	±0.5°C/±0.6°F(10~55°C/50~131°F)
Humidity Range	0.1-99.9%
Humidity Accuracy	±3%RH(20%RH~80%RH) 25°C
Power	adaptor(DC9v)
Operating Environment	5 ~ 30°C; (0~85%RH)
Sensor life	15 years in nomal comm
Size	388×288×43mm
Wight	2420g



HT-2008

ติดต่อบริษัท นีโอนิคส์ จำกัด  
Tel: 02-077-7602 หรือ 061-8268939  
E-mail: sale@tools.in.th หรือ sale@neonics.co.th