

# PRODUCT DATA SHEET

## Wall-mount Dust Particle Counter SW-625A



### Product Features:

- ✔ Wall mounted PM2.5 Monitor
- ✔ The scattering light of particles is collected by laser scattering principle.
- ✔ Alarm adjustable
- ✔ Easy to install at Conference Room, Hotel, Market, School, Hospital ward
- ✔ Wall hanging type. With the hanging hole, it can installed on the wall to or free stand on the table.

- PM2.5 air quality detection: PM2.5
- Range: (0~500ug/m3 )
- Concentration unit: ug/cubic meter (ug/m3)
- Detection sensitivity: 1ug
- Measurement error: <math>\pm 10\%</math>
- Flowrate: 1L/min
- Sampling method: pumping
- Sampling principle: light scattering
- Light source: laser diode
- Detection method: manual
- Automatic power-off function: it will power off automatically if there is no operation within 2 minutes at power-on state.
- Environmental condition:
- Application environment: temperature scope: 5°C~45°C
- Humidity range: <math>< 80\%RH</math>
- Storage environment: temperature scope: -20°C~60°C
- Humidity range: <math>< 80\%RH</math>
- Sampling time: 50s
- Resolution ratio of sensor: 1ug/m3
- Temperature measurement range: -40°C+125°C Precision  $\pm 0.5^{\circ}C$
- Humidity measurement range: 0-100%RH Precision  $\pm 2\%RH$



ติดต่อบริษัท เนโอนิกส์ จำกัด

Tel: 02-077-7602 หรือ 061-8268939

E-mail: sale@neonics.co.th เว็บไซต์ www.neonics.biz

