

เครื่องวัดความหนืด  
Digital Lab Viscometer LVDV-1



www.tools.in.th  
ติดต่อบริษัท นีโอนิคส์ จำกัด  
Tel: 02-077-7602 หรือ 061-8268939  
E-mail: sale@tools.in.th หรือ sale@neonics.co.th



## ◆ The main technical indicators

Measuring Range ( mPa·s )	12 ~ 6,000,000
Rotating Speed (RPM)	0.1 ~ 99.9( Stepless Gear)
Number of Spindles	Spindles (Code L1,L2,L3,L4) are equipped with the product
Accuracy	±1% full scale range in use
Repeatability	±0.5% full scale range in use
Readability	1.when viscosity is lower than 10.0 cp : 0.01 2.when viscosity is lower than 10000 cp : 0.1 3.when viscosity is equal or higher than 10000 cp : 1
Power	Power adapter ( input: 100-240V , 50/60Hz)
LCD screen display	The LCD screen can display the viscosity,speed,torque, spindle and the maximum viscosity can be measured in the current spindle speed value.

## ◆ Apparatus to be equipped

digital viscosity meter	1 pce	ascending and falling rack	1 set
standard spindle	1 set	power adapter	1 pce
protective frame of spindle	1 pce	spanner	1 pce
Seat and leveling feet	1 set	RS232 standard output interface	1 pce
. RTD temperature probe	1 pce		

## ◆ Options

• Extreme low viscometer adapter (with one spindle L0)
• Small sample adapter (with spindle 21, 27, 28 and 29 each)
• Temperature-controlled heater (with spindle 21, 27, 28 and 29 each)
• Spindle L5
• Special software that can complete the function in collecting the data automatically
• DV program control download software
• Specially used printer



[www.tools.in.th](http://www.tools.in.th)

ติดต่อบริษัท นีโอนิคส์ จำกัด

Tel: 02-077-7602 หรือ 061-8268939

E-mail: [sale@tools.in.th](mailto:sale@tools.in.th) หรือ [sale@neonics.co.th](mailto:sale@neonics.co.th)