








Digital Humidity & Temperature Meter Series



Pictures							
Models	GM1360	GM1360A	GM1361	GM1361+	GM1362	GM1365	GM1366
page	P34	P34	P35	P35	P36	P36	P36
Temperature Range	-10~50°C	-30~80°C	-10~50°C	-10~50°C	-30~70°C	-30~80°C	-30~80°C
Humidity Range	5~98%RH	0~100%RH	10~98%RH	10~99.9%RH	0~100%RH	0~100%RH	x
Thermocouple Temperature	x	x	x	-50~1200	x	x	x
Max/Min	√	√	√	√	√	√	√
bluetooth(app)	x	x	√	√	x	bluetooth	bluetooth
USB Interface	x	√	√	√	x	√	√
°C/°F Selection	√	√	√	√	√	√	√
Keeping Data	√	√	√	√	√	√	√
Sampling Frequency	2.5 Times/Second	1Times/Second	2.5Times/Second	2Times/Second	2.5Times/Second	x	x
K-type Thermocouple Temperature measuring	x	x	√	√	x	x	x
Backlight	x	x	√	√	√	√	√
On/lower limit alarm value	x	x	x	√	x	x	x
Data recording/reading/deleted	x	x	x	x	x	x	x
Alarm set	x	x	x	999	x	32256	61440
LCD Dual Display	√	√	√	√	x	x	x
Auto Power Shut Off	√	√	√	√	√	√	√