

Portable Dissolved Oxygen Meter AMT07



AMT07

Features:

- Microprocessor based for fast and accurate measurements.
- Special viewing angle designed of waterproof housing IP57 rated. It floats on water.
- Large LCD display and Temperature Simultaneously.
- Simple to calibrate by one keyboard and automatic temperature compensation (ATC), Manual Salinity (MSC) and Altitude(MAC) Compensation.
- Multi-functions with Data-hold, Max/Min and shows PTS after calibration. Degree °C/°F are switchable.
- Low battery and consumption indicator. Auto power shut off after 10 minutes of non use.
- Easy to replace electrode module and the type of electrode would be recognized automatically and shown in display during insertion.

Specifications

| | DO | O2 | Temp |
|---------------|--|--------|-----------|
| • Range | 0~20.00mg/L | 0~200% | 0~90.0 °C |
| • Accuracy | ±0.2 | ±2% FS | ±0.2 |
| • Resolution | 0.01 | 0.1 | 0.1 |
| • ATC | 0~50 °C | | |
| • MSC | 0~50 ppt | | |
| • MAC | 0-20000 ft | | |
| • Calibration | 100% in air | | |
| • Power | DC1.5V x 4 battery size:AAA/UM-4 | | |
| • Dimensions | Meter: 195 x 40 x 36 mm, Kits: 230 x 205 x 50 mm | | |
| • Weight | Meter: 135g(with battery), Kits: 780g | | |

Portable Dissolved Oxygen Meter AMT08

Features:

- Microprocessor based for fast and accurate measurements.
- Waterproof housing IP57 rated. It floats on water.
- Large LCD display and Temperature Simultaneously.
- Auto Power Off

Specifications:

- Range: 0.0~19.9mg/L
- Resolution: 0.1mg/L
- Accuracy: ±0.5mg/L
- Temp.: 0.0~99.9 °C
- Temp. Resolution: 0.1 °C
- Temp. Accuracy: ±0.5 °C
- ATC: 5~45 °C
- Calibration Alarm: Yes
- Auto Off: After 10 minutes
- Power: 4 x 1.5V Button Cell
- Size: 170*37*37mm
- Weight: 90g



AMT08