



CFM/CMM Hotwire Anemometer HT-9829

Hotwire Anemometer is suitable for use in a wide variety of applications, including plant maintenance operations, environmental analysis, fume hood testing, and HVAC system assessments.



Air Velocity	Range	Resolution	Accuracy
m/s (meter per second)	0.10~25.00 m/s	0.01m/s	±3% +0.20m/s
ft/min (feet per minute)	20~4926 ft/min	0.1km/h	±3% +40ft/min
km/h (kilometers per hour)	0.3~90.0 km/h	1ft/min	±3% +0.8km/h
MPH (miles per hour)	0.5~55.8 MPH	0.1mph	±3% +0.4MPH
Knots	0.2~48.5 Knots	0.1knots	±3% +0.4knots
Air Temperature	0-50°C (32-122°F)	0.1°F/°C	±2.0°C (4.0°F)
Air Flow	Range	Resolution	Area
CFM	0-9999	1	0-9.999 ft2
CMM	0-9999	1	0-9.999 m2
Battery	9V		
Weight	390g		
Size	198×85×45mm		
Accessories	Batteny,manual black box and gift box.		



LINE ID: @neonics



ติดต่อบริษัท นีโอนิกส์ จำกัด

Tel: 02-077-7602 หรือ 061-8268939

E-mail: sale@tools.in.th หรือ sale@neonics.co.th