

Function	WT87A	WT87B
Measurement of wind speed and temperature	√	√
Humidity measurement	✗	√
Wind cold indicator	√	√
Switch wind speed units	√	√
Real-time measurement of wind speed and average wind speed	√	√
Measurement of maximum wind speed and minimum wind speed	√	√
Switch between Fahrenheit and Celsius unit	√	√
Timed automatic shutdown	√	√
LED lighting	√	√
Measurement of air volume	✗	√
USB communication (with computer applications)	✗	√
Bluetooth communication (with mobile APP)	✗	√

Application



Outdoor



Factory



School



Home



USB communication function

Specification						
Wind velocity measurement						
Unit	Measurement range	Resolution	Threshold	Accuracy		
m/s	0~30	0.01	0.3	±5% ±0.1		
ft/min	0~5860	1.968	60	±5% ±20		
knots	0~55	0.019	0.6	±5% ±0.2		
km/h	0~90	0.036	1	±5% ±0.4		
mph	0~65	0.022	0.7	±5% ±0.2		
Wind temperature measurement						
Unit	Measurement range	Resolution	Accuracy			
°C	-10°C~45°C	0.1	±2°C			
°F	14°F~113°F	0.2	±3.6°F			
Battery	9V battery (6F22)					
Temperature sensor	Negative Temperature Coefficient Resistance					
Operation temperature	-10°C~45°C(14°F~113°F)					
Operation humidity	Less than 90%RH					
Storage temperature	-10°C~50°C(14°F~122°F)					
Size	165x85x39mm					
	WT87A		WT87B			
Weight	184g		186g			



USB cable



ติดต่อบริษัท นีโอนิคส์ จำกัด

Tel: 02-077-7602 หรือ 061-8268939

E-mail: sale@neonics.co.th เว็บไซต์ www.neonics.biz