

DIGITAL LIGHT METER
MS6610

(LUX)

บริษัท นีโอนิคส์ จำกัด
โทร 02-077-7602 หรือ 061-8268939
E-mail:sale@neonics.co.th

DIGITAL LIGHT METER
(LUX / FC / CD) **MS6612 / MS6612T**



MS6610

LUX RANGE
5000



Specifications MS6610

Specifications	Range	Resolution	Accuracy
Measurement	0~1999 Lux	1 Lux	±(5%+2)
Range	2000~19990 Lux	10 Lux	±(5%+2)
	20000~50000 Lux	100 Lux	±(5%+2)
Features			
Display	counts		2000
Data Hold			●
Photo Detector	One Silicon Photo Diode with Filter		●
Lead Length	150cm(Approx.)		●
LBI	Low Battery Indicator		●
General			
Power Supply	1x9V 6F22 Battery		
Dimension Size	126x72x27mm/5.0"x2.8"x1.0"		
Photo Detector Size	83x52x21mm/3.2"x2.0"x0.8"		
Product Weight	180g/0.4lb		
Safety Rating	RoHS		

Specifications MS6612

Specifications	Range	Resolution	Accuracy
Measurement	0~200000Lux	0.01Lux	±(3%+2)
Range	0~20000FC	0.01FC	±(3%+2)
Features			
Display	counts		2000
Auto ranging	Auto & Manual		●
APO	Auto Power Off		●
MAX/MIN			●
REL	Relative Measurement		●
PEAK	Peak Measurement		●
ZERO	Zero Calibration		●
FC/Lux	FC/Lux Unit Selection		●
Data Hold			●
Backlight	Display Backlight		●
Analog Bar	Analog Bar Indication		●
LBD	Low Battery Display		●
General			
Power Supply	1x9V 6F22 Battery		
Product Size	170mmx89mmx43mm/6.7"x3.5"x1.7"		
Product Weight	177g/0.39lb		
Safety Rating	CE(EMC) RoHS		



MS6612

LUX RANGE
200000

FC RANGE
20000



MS6612T

LUX RANGE
200000

FC RANGE
20000

CD RANGE
999900



Specifications MS6612T

Specifications	Range	Resolution	Accuracy
Measurement	0~200000Lux	0.01Lux	±(3%+2)
Range	0~20000FC	0.01FC	±(3%+2)
	0~999900CD	0.01CD	±(3%+2)
Light Source Default Values	L0-Standard Lighting		●
	L1-LED Daytime Light		●
	L2-LED Red Light		●
	L3-LED Amber(yellow) Light		●
	L4-LED Green Light		●
	L5-LED Blue Light		●
	L6-LED Purple Light		●
L7-L9-Default Standard Lighting		●	
Features			
Display	counts		2000
Auto ranging	Auto & Manual		●
APO	Auto Power Off		●
MAX/MIN			●
REL	Relative Measurement		●
PEAK	Peak Measurement		●
ZERO	Zero Calibration		●
FC/Lux/CD	FC/Lux/CD Unit Selection		●
Data Hold			●
Backlight	Display Backlight		●
Analog Bar	Analog Bar Indication		●
LBD	Low Battery Display		●
General			
Power Supply	1x9V 6F22 Battery		
Product Size	170mmx89mmx43mm/6.7"x3.5"x1.7"		
Product Weight	177g/0.39lb		
Safety Rating	CE(EMC) RoHS		

