

**MOISTURE TESTER**  
**MS6900 / MS6900A**

ติดต่อบริษัท นีโอนิกส์ จำกัด  
Tel: 02-077-7602 หรือ 061-8268939  
E-mail: sale@neonics.co.th หรือ sale@tools.in.th



**MS6900**

**DEPTH**  
0~50mm

**RESOLUTION**  
0.1%, 0.1°C, 0.1°F  
0.1%RH



**MAX MIN**



Specifications		MS6900
Specifications	Range	Accuracy
Depth		0~50mm
Ambient TEMP	-10°C~50°C/14°F~122°F	±0.2°C/±1°F
Electric Conductivity	0.0~60.0%	±1%
Humidity	10~90%	±5%
<b>Features</b>		
MAX/MIN		●
Sampling Rate	Moisture and Humiture	●
Unit Selection	%, WB, TD, °C, °F, %RH	●
Display Backlight		●
Data Hold		●
LBD	Low Battery Display	●
<b>Materials Moisture Range</b>		
1: (8.5~60%)	Beech, Spruce, Larch, Birch, Cherry, Walnut	
2: (6.8~53.4%)	Oak, Cedar, Maple, Ash Tree, Pink Shower Tree, Tamarisk	
3: (0.9~24.5%)	Smoothing Cement, Concrete	
4: (0.0~12.2%)	Anhydrite Screed	
5: (0.7~9.2%)	Cement Mortar	
6: (0.5~11.1%)	Lime Mortar, Plaster	
7: (0.0~17.8%)	Brick	
<b>General</b>		
Power Supply	2x1.5V AAA Batteries	
Product Size	130mmx56mmx29mm/5.1"x2.2"x1.1"	
Product Weight	120g/0.26lb	
Safety Rating	CE(EMC) RoHS	

**MS6900A**

**DEPTH**  
0~50mm

**RESOLUTION**  
0.1%, 0.1°C, 0.1°F  
0.1%RH



**MAX MIN**



Specifications		MS6900A
Specifications	Range	Accuracy
Depth		0~50mm
Ambient TEMP	-10°C~50°C/14°F~122°F	±0.2°C/±1°F
Electric Conductivity	0.0~60.0%	±1%
Humidity	10~90%	±5%
<b>Features</b>		
Auxiliary	Verification Test Points	●
MAX/MIN		●
Sampling Rate	Moisture and Humiture	●
Unit Selection	%, WB, TD, °C, °F, %RH	●
Display Backlight		●
Data Hold		●
LBD	Low Battery Display	●
<b>Materials Moisture Range</b>		
1: (8.5~60%)	Beech, Spruce, Larch, Birch, Cherry, Walnut	
2: (6.8~53.4%)	Oak, Cedar, Maple, Ash Tree, Pink Shower Tree, Tamarisk	
3: (0.9~24.5%)	Smoothing Cement, Concrete	
4: (0.0~12.2%)	Anhydrite Screed	
5: (0.7~9.2%)	Cement Mortar	
6: (0.5~11.1%)	Lime Mortar, Plaster	
7: (0.0~17.8%)	Brick	
<b>General</b>		
Power Supply	2x1.5V AAA Batteries	
Product Size	130mmx56mmx29mm/5.1"x2.2"x1.1"	
Product Weight	120g/0.26lb	
Safety Rating	CE(EMC) RoHS	

**COMBUSTIBLE GAS DETECTOR**  
**MS6310**



**MS6310**

**RESOLUTION**  
50 ppm

**ALARM**  
10%~40%

**GAS** **LED**

Specifications		MS6310
Specifications		
Resolution (methane)		50ppm
Alarm at Level		10%~40%
Warm Up Time		2 Minutes
Response time (40% LEL)		<2 Seconds
<b>Feature</b>		
Easy To Identify and Pinpoint Gas Leaks		●
Portable and High Sensitivity		●
Resume Original Measurement State after 7~10 minutes in Clean air		●
Gas Detected: Natural gas, Methane, Ethane, Propane, Butane, Acetone, Alcohol, Ammonia, Steam, Carbon Monoxide, Gasoline, Jet fuel, Hydrogen Solvents, Lacquer thinner, Naphtha		●
<b>General</b>		
Power Supply	4x1.5V AAA Batteries	
Product Size	172mmx70mmx46mm/6.8"x2.8"x1.8"	
Product Weight	354g/0.78lb	
Safety Rating	CE(EMC) RoHS	

