



HT-801



Bluetooth Temperature And Humidity Meter

Temperature and humidity meter is used for measuring the surroundings temperature and humidity so that we can know the environment conditions for production and storage.

Specification

Humidity range	0~100%RH
Temperature range	-20°C~80°C(-4°F~176°F)
Dew point temperature	(-20°C~80°C/-4°F~176°F)
Wet Bulb temperature	0°C~80°C/32°F~176°F)
Humidity accuracy	±3%RH(25°C,20%~80%RH). ±2.5%RH(At other ranges)
Air temperature accuracy	±0.8°C/±0.9°F(25°C) ±0.8°C/±1.5°F(At other ranges)
Resolution	0.01%RH,0.01°C/0.01°F
Response time	10S
3 AAA batteries	
The device can with a small display, the APP of Android and IOS can monitoring data remotely (Bluetooth transmission)	
Can generate digital charts, trend graphs;	
Support to save / share data graphs .xls	
Support save / share trend graphs .jpg	
IOS8.3 / Android 4.3 above (bluetooth4.0)	

Ultrasonic Distance Meterpower

It can be used for ultrasonic distance measuring,main apply to measure the distance of urban road plannig, construction site,industrial spot,etc.

Specification

Power supply	9V
Unit of measurement	ft/m
Accuracy	0.5%±1Digits(2-60ft)
Working frequency	40KHz
Working temperature(Fahrenheit degree)	32-109.4°F
Range	2-60ft(0.55~18.288m)
Laser Diode Type	Red laser diode 650nm
Size	185×75×35mm 30s auto tum off
Weight	208g



HT-526

Digital Tachometer

Commonly used in motor,electric fan,paper making,plastic, chemical fiber,washing machines and cars field.

Specification

Measurement	Contact	1~19999
	Non-contact	1~19999
Display	Contact	999999counts
	Non-contact	999999Counts
Target distance	Non-contact	50mm~600mm
Best Accuracy	0.02%±2dgt	
Auto power off	15s	
Max / min / road / M / min M / s feet / minute feet / sec / min		
Size	236×72×35mm	
Weight	218g	



HT-522



ติดต่อบริษัท นีโอนิกส์ จำกัด

Tel: 02-077-7602 หรือ 061-8268939

E-mail: sale@tools.in.th หรือ sale@neonics.co.th