

Digital Hand-held "Pocket" Salt Meters

Contact ATAGO for salinity measurements of semi-solid food, such as meat and cheese.









Specifications

Measurement method

Measurement range 0.0 to 7.0% (g/100g) of salt concentration Resolution 0.01% (0.00 to 1.99%) 0.1% (2.0 to 7.0%) Measurement accuracy ±0.1% (0.00 to 2.0%) Relative precision ±5% (2.1 to 5.0%) Relative precision ±10% (5.1 to 7.0%) Measurement time 3 seconds 2×AAA Batteries Power supply International protection class IP65 Water resistant Main unit: 5.5×3.1×10.9cm, 100g Dimensions and weight Electrode probe : ø1.0×53cm (Cable length : approx. 40cm)

Conductivity method

• The sample must be diluted if its salinity exceeds 7%

The 'Pocket' salt meters utilize the electric conductivity method to measure salt concentrations.
Due to the difference in measurement principles, readings by the conductivity method may not match up exactly with readings by silver nitrate titration methods (Mohr's Method).

All ATAGO Salt Meters are designed and manufactured in Japan.



http://www.atago.net/ overseas@atago.net

Headquarters: The Front Tower Shiba Koen. 23rd Floor 2-6-3 Shiba-koen, Minato-ku, Tokyo 105-0011, Japan

TEL: 81-3-3431-1943 FAX: 81-3-3431-1945





ติดต่อบริษัท นีโอนิคส์ จำกัด

Tel: 02-077-7602 หรือ 061-8268939

E-mail: sale@neonics.co.th หรือ sale@tools.in.th