



**PH Meter**  
**AS218**  
0.00~14.00pH



**Tachometer**  
**AS926**  
2.5~99999RPM



**EMF-Tester**  
**AS1392**  
30Hz ~ 300Hz




**EMF-Tester**  
**AS1392A**  
30Hz ~ 300Hz

**Insulation Resistance Tester**  
**AS907**



**Insulation Resistance Tester**  
**AS907A**



## PH Meter

SPEC	AS218
Measuring Range	0.00~14.00pH
Accuracy	±0.05
Stability	±0.03
Repeatability	±0.03
Solution Temp. Compensation Range	0°C~60°C
Response Time	≤30 sec
Temp. Measuring	-10°C~60°C
The Measured Solution Temp.	5°C~60°C
Operation Condition	0°C~35°C/0~80%RH
Battery Indication	✓
Data Hold	✓
Backlight Display	✓
°C / °F Selection	✓

### PACKING INFORMATION

Power	9V battery
Product Net Weight	205g
Product Size	159 x 66 x 31mm
Packing	Gift box
Standard Quantity / Carton	20
Standard Carton Size	45 x 32 x 55cm
Std Carton G/Weight	15.21kg

## Insulation Resistance Tester

SPEC	AS907	AS907A
Rated Voltage	250V / 500V / 1000V	500V/1000V/2500V
Open Circuit Voltage	90% ~ 110% of Rated Voltage	
Testing Range	1KΩ~2000KΩ	10KΩ~20GΩ
Resolution	0.001MΩ ~ 200MΩ (3% rdg +5 digits) 200MΩ ~ 10GΩ (5% rdg +5 digits) 10GΩ ~ 20GΩ (10% rdg +5 digits)	
ACV Range	≤600V	
ACV Accuracy	2% rdg + 15 digits	
ACV Frequency	50 / 60 Hz	
Operation Condition	0°C ~ 40°C, < 80% RH	
Storage Condition	-10°C ~ 50°C, < 85% RH	
Auto Discharge Function	✓	
Battery Indication	✓	
Data Hold	✓	

### GENERAL CHARACTERISTICS & PACKING INFORMATION

Power	6*1.5V AA batteries	6*1.5V AA batteries
Product Net Weight	410g	410g
Product Size	122 x 66 x 173mm	122 x 66 x 173mm
Packing	Gift box	Gift box
Standard Quantity / Carton	12	12
Standard Carton Size	52 x 33.5 x 47cm	52 x 33.5 x 47cm
Standard Carton Gross Weight	17.08kg	17.08kg

## EMF-Tester

SPEC.	AS1392A	AS1392
Measuring Frequency	30Hz ~ 300Hz	
Measuring Range	0.1m~1999m Gauss	0.01μ~200μ Tesla
Resolution	0.1μT	
No. of Axis	Single Axis	
Accuracy	±5%(50μT~200μT)μT 50Hz/60Hz	
Sampling Rate	0.5 sec	
Electric Field Range	1~1999 v/m	---
Electric Field Resolution	1 v/m	---
Dual Readings Display	✓	---
Range Status Display	✓	---
Data Hold	✓	✓
Unit Selection	✓	✓
Backlight Display	✓	✓
Battery Indication	✓	✓
Operation Condition	0°C~40°C / ≤80%RH	

### GENERAL CHARACTERISTICS & PACKING INFORMATION

Power	3*1.5V AAA batteries	3*1.5V AAA batteries
Product Net Weight	119g	75g
Product Size	143 x 68 x 28mm	135 x 47 x 25mm
Packing	Gift box	Blister
Standard Quantity / Carton	80	60
Standard Carton Size	53 x 49 x 44cm	50 x 24 x 46cm
Standard Carton Gross Weight	19.65kg	10.9kg

## Tachometer

SPEC.	AS926
Measuring Range	2.5~99999RPM
Resolution	0.1RPM (2.5~999.9RPM) 1RPM (Over 1000RPM)
Accuracy	±(0.05%+1 digits)
Sampling Time	0.8 sec (Over 60RPM)
Measuring Distance	50mm ~ 500mm
Max / Min Measuring	✓
Data Storage	✓
Memories Clear	✓
Range Selection	Auto
Battery Indication	✓

### GENERAL CHARACTERISTICS & PACKING INFORMATION

Power	3*1.5V AAA batteries
Product Net Weight	75g
Product Size	135 x 47 x 25mm
Packing	Blister
Standard Quantity / Carton	60
Std Carton Size	50 x 24 x 46cm
Std Carton G/Weight	10.9kg